

SCALEOVIEW L17-5 17-inch LCD Display

Issue January 2007

Pages 2

The SCALEOVIEW L17-5 is an excellent 17-inch TFT display for all-purpose. It offers best performance for home office as well as for multimedia such as photo editing, gaming and watching the latest DVDs. Experience amazing contrast, extremely fast response time and crystal clear images – and all that with an attractive price point.

Highlights

- § Best performance to an affordable price
 - Office applications
 - Internet and multimedia are supported best
- § Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

Ergonomics

- § Optimum flicker-free and distortion-free ergonomics
- § Excellent color purity
- § Well balanced brightness uniformity
- § Excellent high contrast 800:1
- § Space saving design

Technical highlights

- § 17" (43 cm) LCD Display
- § Excellent contrast 800:1
- § Brightness 300 cd/m²
- § Fast response time (typ.) 5 ms

Reliability

- § Low power consumption
- § Power management according to EPA
- § Guaranteed quality and stability



Visible screen diagonal	17-inch (43 cm)
Resolution	
Pixels	1280 x 1024
Pixels*	1024 x 768
Pixels*	800 x 600
* expanded	
Picture size	338 x 270 mm
Colors	16.2 million
Pixel Pitch	0.264 mm
Frequencies	
Horizontal	31 - 81 kHz
Vertical	56 - 75 Hz
Brightness (typical)	300 cd/m ²
Contrast (typical)	800:1
Viewing angle (typical)	
Horizontal	170°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light)	
Contrast, Volume control	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, French, Italian, Spanish, Polish, Dutch, Russian	
Base	
Tilt angle	-5° / +20°
Video input	1x D-SUB, 1x DVI-D
Audio input / output	
Audio signal input	3.5 mm stereo phone jack
Audio output	1 W (L) + 1 W (R)
Electrical values (internal power supply)	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	< 40 W
Stand by	< 1 W
Protection class	1

Temperatures/ dimensions/ weight

Ambient temperature (to IEC721):

Working (recommended) 5°C to 35°C

Storage -20°C to 60°C

Dimensions (H x W x D): 372 x 378 x 214 mm
(With Stand)

Weight (Monitor only): 3.5 kg

Reliability

MTBF (demonstrated) 70,000 h

Lifetime of LCD backlight 50,000 h

(brightness > 50 % of original brightness)

Compliance with standards

Product safety EN60950, NEMKO

Ergonomics GS mark

ISO13406-2

(Pixel fault class II)

Radiation immunity and CE certification according
RFI suppression to EC Directive

89/336/EEC

(EN55022/B, EN50082-1

EN61000-3-2/-3);TCO 99;

FCC Class B part 15

Accessories

Power cable (1.8 m)* For wall socket

Euro-Schuko-Type CEE7

Plug type on Monitor IEC-320-C13

Data cable (1.8 m)* 1x D-SUB (15-pin)

Audio Cable (1.8 m)* 3.5 mm stereo phone jack

* detachable on display

Special featuresStandardized mounting
interface (according VESA

FPMPI 100 mm)

Integrated audio

Kensington Lock

Order code S26361-K1164-V170**EAN** 4045827933557